

# TWISTER™ CLOSING WHEELS

**Yetter**  
FARM EQUIPMENT  
SINCE 1930

With weather and field conditions changing every year, 6200 Twister Closing Wheels are a key component for even emergence.

In 4 of 4 studies conducted in central Illinois, Indiana, Ohio, and southern Illinois, Yetter 6200 Twister Closing Wheels showed the highest yield response in comparison to other closing wheel brands, adding an **AVERAGE OF 6.4 BU/ACRE.**



BECK'S



## BETTER CLOSING WHEEL PERFORMANCE

The twisted-spike design of the 6200 Twister Closing Wheel is key to breaking down the sidewall compaction caused by the planter opener discs. The spikes close and firm soil over the seed to eliminate air pockets, enhancing seed-to-soil contact for earlier germination and even emergence.

## TWISTER CLOSING WHEEL FEATURES

- » Wheel utilizes twisted spikes and a rounded center
- » Ring design maintains wheel depth and also firms the soil
- » Closes the disc opening in both wet and ideal conditions
- » Available with full wheel assembly or as ring-only option for installation on factory wheels



800.447.5777 | info@yetterco.com | www.yetterco.com

# READY TO PUT A NEW SPIN ON CLOSING WHEEL PERFORMANCE?



## 6200 TWISTER CLOSING WHEEL

### DON'T LEAVE SEED TRENCH CLOSURE UP TO CHANCE.

You prepare all year for the moment the seed goes in the ground. If you're rolling the dice with factory rubber closing wheels, or leaving it up to the weather Mother Nature sends your way, you're missing an opportunity to maximize yield.

Sidewall compaction can be a challenge during planting. Factory rubber closing wheels are designed to firm up loose soil—they do nothing to fracture sidewall compaction.

To close the seed trench and improve emergence, set your planter up with Twister Closing Wheels. We recommend using two closing wheels across from each other, set at 1 1/4" spacing. They work in unison to pull in soil around the seed, creating optimal seed-to-soil contact.



Since its introduction, the poly-spike Twister Closing Wheel has received positive feedback from customers and dealers. For the past two years at different locations in Beck's Practical Farm Research studies, the Twister increased yields by an average of 6.4 bushels per acre\*.



Beck's PFR provides unbiased, farmer-focused research through studies conducted across the Midwest. The studies compared the Twister Closing Wheel with other closing wheels on the market.

\*Please remember yield results vary based on many factors each year. Always consider your unique operation when deciding what equipment to invest in. Data found here is only a starting point.



#### CRUMBLES AND FIRMS SOIL AT THE SAME TIME

Twisted spikes enhance seed-to-soil contact and help create the ideal seed environment, leading to even emergence and higher yields. The rounded center ring—sized at 12" to match the size of rubber closing wheels—maintains consistent depth of the 1 3/8" spikes.



#### WORKS IN DIVERSE FIELD CONDITIONS, COVER CROPS, AND TILLAGE PRACTICES

Optimize performance for minimum till, conventional, strip-till, vertical tillage, or no-till by adjusting down pressure on the tail wheel closing arm.



#### SMOOTH SURFACE AND ROUNDED CENTER DESIGN HELP PREVENT MUD BUILDUP

In wet, unfavorable planting conditions, the Twister fractures the sidewall. This reduces the potential for crusting and the seed trench drying out and cracking open.



#### COST-EFFECTIVE AND EASY TO INSTALL

The Twister Closing Wheel is built for durability with ultra-high molecular weight (UHMW) plastic material. Also easy to install, the Twister is a cost-effective, high-performing replacement closing wheel that provides ROI.

### EACH PLANTING SEASON, FARMERS FACE A CRITICAL CHALLENGE: HOW TO SUCCESSFULLY CLOSE THE SEED TRENCH.



The Yetter 6200 Twister Closing Wheel has a twisted-spike design that breaks up sidewall compaction and is effective in a wide range of soil conditions. Whatever your tillage practice or soil type, the Twister Closing Wheel zips the seed trench closed, ensuring seed-to-soil contact for optimal seed germination.

#### SETUP OPTIONS:

- » Full wheel assembly replaces factory closing wheels on most planters
- » Available with optional drag chain
- » Ring-only insert option installs on most factory wheels

#### COMPATIBLE WITH:

- » John Deere MaxEmerge™ Plus, XP, and XP Pro
- » Kinze '93 - current
- » AGCO White and Massey Ferguson
- » Great Plains
- » Monosem
- » Precision Planting Ready Row Unit

### HERE'S HOW TO CHECK WHETHER YOU NEED A BETTER CLOSING WHEEL:

1. Inspect behind the planter when tillage practices and soil conditions change. An open V shape in the seed trench means you do NOT have seed-to-soil contact—resulting in yield loss.
2. Insert a 4" putty knife directly into a planted row, perpendicular to the direction of travel.
3. Using another 1" putty knife or similar scraper, scrape the soil out of the seed zone to reveal an opening approximately 6" long and equal to the width and depth of the inserted 4" putty knife.
4. Remove the 4" putty knife to reveal a cross-section of the planted row.
5. To understand what changes are needed to improve your closing wheel system, inspect the seed trench for excessive sidewall compaction, air pockets, and poor seed-to-soil contact.

With the Twister Closing Wheel, the seed trench is closed, giving you assurance that the investment you made in seed, chemical, fertilizer, and equipment will produce the yields you have planned for.



"I was able to close the furrow in heavy, no-till soybean residue, which helped ensure near-perfect emergence. This resulted in my highest no-till corn yields to date. Another bonus was being able to use this closing wheel in conventional till."



Steve Pitstick, IL